
# 18' x 30' SUPER MAX™ ENCLOSURE KT Assembly Instructions



DESCRIPTION	MODEL#
18' x 30' Super Max™ - 12 Leg - Enclosure Kit - White	26779

# **RECOMMENDED TOOLS**



Please read instructions <u>COMPLETELY</u> before assembly. This shelter <u>MUST</u> be securely anchored. THIS IS A TEMPORARY STRUCTURE AND NOT RECOMMENDED AS A PERMANENT STRUCTURE.

Before you start: 1+ individual recommended for assembly, approximate time 2 hr.



# WAKNING:

KEEP ALL FLAME AND HEAT SOURCES AWAY FROM THIS TENT FABRIC

This tent meets the flammability requirements of CPAI-84. The fabric may burn if left incontinuous contact with any flame source. The application of any foreign substance to the tent fabric may render the flame-resistant properties ineffective.



www.shelterlogic.com

1-800-524-9970 Canada: 1-800-559-6175

### **ATTENTION:**

This shelter product is manufactured with quality materials. It is designed to fit the **ShelterLogic®**, **LLC** custom fabric cover included. **ShelterLogic®**, **LLC** Shelters offer storage and protection from damage caused by sun, light rain, tree sap and animal - bird excrement. Please anchor this **ShelterLogic®**, **LLC** structure properly. See manual for more anchoring details. Proper anchoring, keeping cover tight and free of snow and debris is the responsibility of the consumer. This shelter is not recommended for severe weather conditions. Please read and understand the installation detail, warnings and cautions prior to beginning installation. If you have any questions call the customer service number listed below. Please refer to the warranty card inside this package.

### **DANGER:**

Prior to installation, consult with all local municipal codes regarding installation of temporary shelters. Choose the location of your shelter carefully. **DANGER:** *Keep away from electrical wires.* Check for overhead utility lines, tree branches or other structures. Check for underground pipes or wires before you dig. DO NOT install near roof lines or other structures that could shed debris onto your shelter. DO NOT hang objects from the roof or support cables.





### **WARNING:**

Risk of fire. DO NOT smoke or use open flame devices (including grills, fire pits, deep fryers, smokers or lanterns) in or around the shelter. DO NOT store flammable liquids (gasoline, kerosene, propane, etc.) in or around your shelter. Do not expose top or sides of the shelter to open fire or other flame source.





# **CAUTION:**

Use **CAUTION** when erecting the frame. Use safety goggles during installation. Secure and bolt together overhead poles during assembly. Beware of pole ends.

### PROPER ANCHORING AND INSTALLATION OF FRAME:

# PROPER ANCHORING OF THE FRAME IS THE RESPONSIBILITY OF THE CONSUMER.

**ShelterLogic®**, **LLC** is not responsible for damage to the unit or the contents from acts of nature. Any shelter that is not anchored securely has the potential to fly away causing damage, and is not covered under the warranty. Periodically check the anchors to ensure stability of shelter. **ShelterLogic®**, **LLC** cannot be responsible for any shelter that blows away. **NOTE:** Your shelter's cover can be quickly removed and stored prior to severe weather conditions. If strong winds or severe weather is forecast in your area, we recommend removal of cover.

# **REPLACEMENT PARTS, ASSEMBLY, SPECIAL ORDERS:**

Genuine **ShelterLogic®**, **LLC** replacement parts and accessories are available from the factory, including anchoring kits for nearly any application, replacement covers, wall and enclosure kits, vent and light kits, frame parts, zippered doors and other accessories. All items are shipped factory direct to your door.

# QUESTIONS - CLAIMS - SPECIAL ORDERS? CALL OUR CUSTOMER SERVICE HOTLINE:

U.S. CUSTOMER SERVICE: 1-800-524-9970 INTERNATIONAL CUSTOMER SERVICE: 001-860-945-6442 CANADA CUSTOMER SERVICE: 1-800-559-6175 HOURS OF OPERATION: MON-FRI 8:30AM-8:00PM EST, SAT-SUN 8:30AM-5:00PM EST.

# **CARE AND CLEANING:**

A tight cover ensures longer life and performance. Always maintain a tight cover. Loose fabric can accelerate deterioration of cover fabric. Immediately remove any accumulated debris from the roof structure with a broom, mop or other soft-sided instrument. Use extreme caution when removing debris from cover- always remove from outside the structure. DO NOT use hard-edged tools or instruments like rakes or shovels to remove debris. This could result in punctures to the cover. DO NOT use bleach or harsh abrasive products to clean the fabric cover. Cover is easily cleaned with mild soap and water.



### **WARRANTY:**

This shelter carries a full limited warranty against defects in workmanship. **ShelterLogic®**, **LLC** warrants to the Original Purchaser that if properly used and installed, the product and all associated parts, are free from manufacturer's defects for a period of:

# 1 YEAR FOR COVER FABRIC, END PANELS AND FRAMEWORK

Warranty period is determined by date of shipment from **ShelterLogic®**, **LLC** for factory direct purchases or date of purchase from an authorized reseller, (please save a copy of your purchase receipt). If this product or any associated parts are found to be defective or missing at the time of receipt, **ShelterLogic®**, **LLC** will repair or replace, at it's option, the defective parts at no charge to the original purchaser. Replacement parts or repaired parts shall be covered for the remainder of the Original Limited Warranty Period. All shipping costs will be the responsibility of the customer. Parts and replacements will be sent C.O.D. You must save the original packaging materials for shipment back. If you purchased from a local dealer, all claims must have a copy of original receipt. After purchase, please fill out and return warranty card for product registration. Please see warranty card for more details.

 $Covered\ by\ U.S.\ Patents\ and\ patents\ pending:\ 6,871,614;\ 6,994,099;\ 7,296,584;\ D\ 430,306;\ D\ 415,571;\ D\ 414,564;\ D\ 409,310;\ D\ 415,572;\ D\ 414,564;\ D\ 414$ 

Page 2 05-26779-0C

18' x 30' 2" SUPER MAX - 12 Leg - Enclosure Kit Parts List - Model #26779

Description of Parts:		Quantity	Part #
	Side Walls	2	10334
	Back Panel	1	10336
	3 - Zipper Door	1	10337
	Bungee Cords	102	10066


### **NOTES:**

- Canopy Enclosure panels attach to frame with bungee cords.
- Leave Canopy Cover bungees in place when attaching Enclosure panels.

**CAUTION:** Bungee Cords are under extreme tension. Use Caution when installing. Safety glasses are recommended to prevent injury.

# 1. ATTACH SIDE WALLS TO FRAME

- A. If tightened at corner leg poles, disengage the TwistTite<sup>™</sup> cord and "S" hook from canopy cover and corner legs. Re-tighten after all Enclosure panels have been secured, as shown in Step 3.
- **B.** Attach the extension panels with bungees to the cross rails at the top first. Adjust the panels as needed to ensure a tight and even fit before securing to the leg poles.




Page 3 05-26779-0C

# 2. ATTACH ENCLOSURE END AND ZIPPER DOOR PANELS


When securing enclosure panels to corner legs, note that each bungee is shared with the neighboring panel.

**NOTE:** Door panels zippers must be closed when securing door panel.



# 3. TIGHTEN THE COVER WITH TWIST TITE™

- **A.** Wrap the cord with plastic ball and "S" hook at the corners of the cover around the corner leg poles. Insert "S" hook into the hole of the corner leg poles.
- **B.** Twist each leg pole toward the inside of the shelter until the cover becomes tight Twist the leg poles equally to ensure the cover stays aligned during tightening.



Page 4 05-26779-0C